



Aqualac PU

## PRODUCT DATA

---

### Description

The ultimate heavy-duty water based floor lacquer. Quick drying, non-toxic, low odour non-yellowing easy to apply, giving a durable scuff resistant finish. Ideal for high quality furniture, dance floors, sports halls and very heavy foot traffic areas.

**Important:** Please note this product should not be used when the floor temperature is below 10 degrees centigrade or in an area subjected to cold drafts, this will affect the performance of Aqualac causing a white milky finish.

### Area of use

Heavy traffic wood flooring and wood furniture.

### Substrates

Wood

### Packing

2.5 litres and 5 litres

### Physical Constants

|                             |                             |
|-----------------------------|-----------------------------|
| Colour:                     | Clear                       |
| Finish:                     | Gloss                       |
| Volume solids:              | 44%                         |
| Theoretical spreading rate: | 18 – 20 sq metres per litre |
| Flash point:                | N/A                         |
| Specific gravity:           | 1.07                        |
| Dry to touch:               | 15 – 20 minutes             |
| Overcoating time:           | 2 – 3 hours                 |

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

### Application Details

|                     |       |
|---------------------|-------|
| Application method: | Brush |
| Thinner:            | Water |
| Cleaning of tools:  | Water |

**Surface condition** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393