

Copal Varnish



PRODUCT DATA

Description:

A traditional varnish formulation.

Provides a flexible and durable external finish, with good UV resistance.

Supplied ready to use by brush.

Thin with white spirit for initial coats on new/porous timber.

Area of use:

Interior and exterior

Substrates:

Wood

Packing:

2.5 Litre

Physical Constants:

Colour:	Clear
Finish:	Gloss
Volume solids:	40%
Theoretical spreading rate:	16 sq..metres per litre
Flash point:	38°C
Specific gravity:	0.92
Dry to touch:	4 – 6 hours
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush Conventional spray Airless spray
Thinner:	White Spirit
Cleaning of tools:	White Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393