



Emulsion Glaze

PRODUCT DATA

Description

Emulsion Glaze is a white milk emulsion, which dries to a glass clear film. Suitable as a clear sealer on brickwork, plaster, cement etc. Can also be used as a clear finish over existing emulsion paints to produce a high gloss finish with improved washability. Specialist application for use in scenery production.

Area of use

Interior

Substrates

Concrete, and plaster type surfaces

Packing

5 litres (min batch 100L)

Physical Constants

Colours:	Clear
Finish:	Semi gloss
Volume solids:	25%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.02
Dry to touch:	2 hours (20°C)
Overcoating time:	4 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush and conventional or airless spray
Thinner:	Water
Cleaning of tools:	Water

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.