



## 2 Pack Tannin Blocker

### PRODUCT DATA

---

#### **Description:**

Water based 2 pack Tannin Blocker. Environmentally friendly stabilised system. Picks up any solubilised stain from the substrate, locks and traps the stain preventing migration into the topcoat.

#### **Area of use:**

Treatment of timber where tannin is prevalent such as Western Red Cedar, Oak, etc.

#### **Substrates:**

Wood

#### **Packing:**

5 Litre/25 Litre

#### **Physical Constants:**

Colour:	Milky
Finish:	Satin
Volume solids:	25%
Theoretical spreading rate:	15 - 20 sq.metres per litre
Flash point:	N/A
Specific gravity:	1.02 - 1.04
Dry to touch:	30 minutes
Overcoating time:	1 – 2 hours in good drying conditions.
Pot life:	When mixed 4 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### **Application Details:**

Application method:	Brush Conventional spray Airless spray
Thinner:	
Cleaning of tools:	Water

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.