



## Chalk Paint

### PRODUCT DATA

---

#### Description

This product is a traditional high quality water-based Chalk Paint providing a beautiful classic matt finish. Chalk Paint is ideal for restoration and decoration of a wide variety of furniture and other surfaces. Provides excellent opacity and the fast drying nature allows for quick over-coating. In most cases, only 1 or 2 coats are required to achieve a uniform matt finish. Chalk Paint is great for special effects and can also be distressed to give the 'Shabby Chic' look. This product is environmentally friendly, very easy to apply, quick drying, low odour and is non-yellowing. Chalk Paint can be waxed with FLAG Classic Wax to give a shiny protected finish.

#### Area of use

Interior

#### Substrates

Wood, Concrete, Plaster, Terracotta, Metal, Various Composites

#### Packing

750mls (other size options are available)

#### Physical Constants

Colour: All colours on special request

Finish: Chalk Finish

Volume solids: 35%

Theoretical spreading rate: 8-12 sq.metres per litre

Flash point: N/A

Specific gravity: 1.45

Dry to touch: 30 minutes

Overcoating time: 4-6 hours

***\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.***

#### Application Details

Application method: Brush,  
\*Minimum DFT 75µm, adjust accordingly for rough surfaces.

Thinner: Water

Cleaning of tools: Water

#### Surface condition

Ensure surface is free from all flaking material, dust, dirt, oil and grease. Do not apply in temperatures below 10 degree centigrade.

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393