



Wood and Metal Paint

PRODUCT DATA

Description

A very easy to apply water-based, quick drying, low-odour, non-yellowing, high performance coating. A high quality, durable and flexible finish with good adhesion characteristics to a wide variety of difficult to paint substrates. Suitable for application on Interior Wood and Metal. Surfaces should be primed with a suitable water-based paint.

Recommended for use over FLAG Acrylic/MDF Primer, Omni-White Primer or Stain Cover + and other similar water-based products.

Area of use

Interior

Substrates

Metal, Wood

Packing

1L, 2.5L, 5L (some sizes are special order items)

Physical Constants

Colour:	White
Finishes:	Low Sheen (virtually matt) or Satin (slight sheen)
Volume solids:	42%
Theoretical spreading rate:	8-12 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.20
Dry to touch:	30 minutes
Overcoating time:	4-6 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, Spray* *Minimum DFT 75µm, adjust accordingly for rough surfaces.
Thinner:	Water
Cleaning of tools:	Water

Surface condition

Ensure surface is free from all flaking material, dust, dirt, oil, and grease. Metals (especially new/forged items) may require degreasing. Do not apply in temperatures below 5 degree centigrade.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393