



## Anti Corrosive QD Metal Primer

### PRODUCT DATA

---

#### Description:

High build quick air-drying oxide primer for use on ferrous metals, provides good protection prior to over coating with most solvent based finishing products. Suitable for a wide variety of applications where speed and ease of application are required. Compatible with FLAG Hammer Finish and FLAG Smooth Metal paints.

#### Area of use:

Internal/External Industrial Structural Steel

#### Substrates:

Metal

#### Packing:

1 Litre & 2.5 Litre

#### Physical Constants:

|                             |                             |
|-----------------------------|-----------------------------|
| Colour:                     | Red & Grey                  |
| Finish:                     | Matt                        |
| Volume solids:              | 60%                         |
| Theoretical spreading rate: | 12 – 15 sq.metres per litre |
| Flash point:                | 23°C                        |
| Specific gravity:           | 1.45 – 1.50                 |
| Dry to touch:               | 15 minutes                  |
| Over-coating time:          | 4 hours                     |

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

|                     |  |
|---------------------|--|
| Application method: | Brush      Conventional spray      Airless spray |
| Thinner:            | Xylene (T10009)                                  |
| Cleaning of tools:  | Xylene (T10009)                                  |

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.