



## Asipo External All Weather Coating

### PRODUCT DATA

---

#### Description

A Pliolite based reinforced masonry coating, flexible and micro-porous, allowing the surface to breath while providing a rainproof barrier, along with excellent self-cleaning properties. It's easy to apply, and provides a long lasting durable finish. A unique blend of resins ensures maximum penetrate and adhesion to even the most difficult masonry surfaces, without the need for a separate primer. Asipo products are formulated to incorporate active biocides, which are non-toxic and provide long term protection against damaging mould and algae attack.

#### Sealing/Priming

On new render or masonry service a sealant coat is recommended, this can be achieved by thinning the paint by 10% with white spirit.

#### Area of use

Exterior

#### Substrates

Cementitious, render, block work, wall areas etc

#### Packing

5 litres (min batch 200L)

#### Physical Constants

Colours::	White (other colours on request)
Finish:	Matt
Volume solids:	60%
Theoretical spreading rate:	10 sq. metres per litre
Flash point:	42°C
Specific gravity:	1.3
Dry to touch:	4 hours (20°C)
Overcoating time:	16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details

Application method: Brush, roller, conventional or airless spray  
Thinner: White Spirit  
Cleaning of tools: White Spirit

#### Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. It is recommended to apply a primer prior to the specified filling procedure. Touch-up with primer on areas repaired with filler is recommended prior to application of topcoats.

*Please refer to the Material Safety Data Sheet for further information.*

*For additional guidance please contact your local Technical Sales Representative.*

*Please check colour before use. If using multiple cans please check batch numbers are the same.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.