



## Emulsion Glaze

### PRODUCT DATA

---

#### Description

Emulsion Glaze is a white milk emulsion, which dries to a glass clear film. Suitable as a clear sealer on brickwork, plaster, cement etc. Can also be used as a clear finish over existing emulsion paints to produce a high gloss finish with improved washability. Also suitable for specialist application in theatre and film scenery production.

#### Area of use

Interior

#### Substrates

Concrete, stone and plaster type surfaces

#### Packing

5 litres (min batch 100L)

#### Physical Constants

Colours:	Clear
Finish:	Gloss
Volume solids:	25%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.02
Dry to touch:	2 hours (20°C)
Overcoating time:	4 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details

Application method:	Brush and conventional spray
Thinner:	Water
Cleaning of tools:	Water

**Surface condition** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

**Caution: Store above 5°C. Do not apply if surface temperature is below 10°C.**

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.