



Floxtone

PRODUCT DATA

Description

For application on external greenhouse areas to prevent too much heat entering during summer months. Designed to help protect plants from direct sunlight and to keep a constant Heat all year round temperature. Can be easily washed away during dormant use of greenhouse.

Area of use

Exterior

Substrates

Glass

Packing

5 litres and 10 litres (min batch 150 litres)

Physical Constants

Colours:	White and Green
Finish:	Matt
Volume solids:	60%
Theoretical spreading rate:	5 - 10 sq. metres per litre
Flash point:	N/A
Specific gravity:	1.6
Dry to touch:	2 – 4 hours (20°C)
Overcoating time:	4 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

<u>Application Details</u>	Brush
Thinner:	Water
Cleaning of tools:	Water

<u>Surface condition</u>	The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.
---------------------------------	--

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.