



Glass & Tile Primer

PRODUCT DATA

Description:

Water based quick drying white primer for use on tiles prior to over-coating with white spirit based finishes. Promotes adhesion and provides excellent opacity.

Area of use:

Interior

Substrates:

Tiles, Glass, Glazed Surfaces

Packing:

1 Litre

Physical Constants:

Colour: White

Finish: Satin

Volume solids: 42%

Theoretical spreading rate: 16 – 20 sq. metres per litre

Flash point: N/A

Specific gravity: 1.23

Dry to touch: 1 hour

Over-coating time: 4 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush

Thinner: Water

Cleaning of tools: Water

Surface Condition: Surfaces must be clean, dry and free from dust, dirt, grease and any other contamination.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393