



Swimming Pool Paint

PRODUCT DATA

Description

Very hardwearing paint for concrete and non-glazed tile surfaces. Suitable for swimming pools where flexibility and chemical resistance is required. Easy to use. Based on Chlorinated Rubber. A single pack solvent based product.

Area of use

Interior and exterior swimming pools

Substrates

Concrete and non-glazed tile surfaces

Packing

5 Litres

Physical Constants

Colours:	Made to order
Finish:	Semi gloss
Volume solids:	55%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	23°C
Specific gravity:	1.3 – 1.4
Dry to touch:	1 - 2 hours (20°C)
Over-coating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, roller, conventional spray or airless spray
Thinner:	Xylene
Cleaning of tools:	Xylene

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

For additional guidance please contact your local Technical Sales Representative.

Please check colour before use. If using multiple cans please check batch numbers are the same.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.