



## Transparent Polish

### PRODUCT DATA

---

#### Description

Clear polish for use on light coloured furniture. Also used as a protective coating for ballet shoes.

#### Area of use

Interior

#### Substrates

Wood

#### Packing

500ml and 5 litres

#### Physical Constants

Colour:	Clear
Finish:	Gloss
Volume solids:	26%
Theoretical spreading rate:	18 sq.metres per litre
Flash point:	18°C
Specific gravity:	0.86
Dry to touch:	10 – 15 minutes
Over-coating time:	30 minutes

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details

Application method:	Cloth or Pad
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

#### Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. Use a shellac sanding sealer prior to using transparent polish.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.