



Wood Primer

PRODUCT DATA

Description

Opaque white solvent thinned primer for woodwork complies BS5358: 1976. Recommended for exterior woodwork where a high quality primer is required and freedom from lead is essential. It may also be used on interior applications.

Area of use

Interior and exterior

Substrates

Wood

Packing

1 litre and 2.5 litres (min batch 100 litres)

Physical Constants:

Colour:	White
Finish:	Matt
Volume solids:	52%
Theoretical spreading rate:	15 sq. metres per litre
Flash point:	38°C
Specific gravity:	1.35
Dry to touch:	4 hours (20°C)
Over-coating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush, roller, conventional and airless spray
Thinner:	White spirit
Cleaning of tools:	White spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints Ltd. 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173, Fax:+44 1621 785393